

LIEFERPROGRAMM DEGUSSA HALBZEUGE

Name	Legierung	Farbe	Dichte	Draht rund oder Walzprofil; in mm					Blech in mm				Rohr Wandstärke 0,5 mm					Guss	Granalien
				1,0	1,5	2,0	3,0	6,0 WP	1,0	1,5	2,0	3,0	2,0	3,0	4,0	5,0	6,0		
800AG-D-1	800/200	weiß	10,1	○	○	○	○	○	○	○	○	○	–	–	–	–	–	○	–
925AG-D-1	925/-	weiß	10,3	○	○	○	○	○	○	○	○	○	–	–	–	–	–	○	–
935AG-D-1	935/-	weiß	10,4	●	●	●	●	●	●	●	●	●	○	●	●	●	●	●	–
999,9AG-D-1	999,9	weiß	10,5	○	○	○	○	○	○	○	○	○	–	–	–	–	–	○	●
333GG-D-2	333/90	gelb	10,6	○	○	○	○	●	○	○	○	●	–	–	–	–	–	●	–
333GG-D-1	333/110	gelb	10,9	○	○	○	○	○	○	○	○	○	–	–	–	–	–	○	–
333WG-D-1	333/600 Ag	weiß	12,1	–	–	–	–	○	–	–	–	○	–	–	–	–	–	○	–
375GG-D-1	375/90	gelb	11	–	–	–	–	○	–	–	–	○	–	–	–	–	–	○	–
585GG-D-1	585/300	gelb	13,9	●	●	●	●	●	●	●	●	●	○	●	●	●	●	○	–
585GG-D-2	585/335	gelb	14	○	○	○	○	○	○	○	○	○	–	–	–	–	–	○	–
585RSG-D-1	585/100	rosé	13,3	○	○	●	●	●	○	○	●	●	○	○	○	○	○	●	–
585RSG-D-2	585/110	rosé	13,2	○	○	○	○	○	○	○	○	○	–	–	–	–	–	○	–
585RG-D-1	585/40	rot	13	○	○	●	●	●	○	○	●	●	○	○	○	○	○	●	–
585PWG-D-1	585/19% Pd	weiß	14,5	●	○	●	●	●	●	●	●	●	○	○	○	○	○	●	–
585PWG-D-2	585/10% Pd	weiß	14,5	○	○	○	○	○	○	○	○	○	–	–	–	–	–	○	–
750GG-D-1	750/130	gelb (3N)	15,4	●	●	●	●	●	●	●	●	●	○	●	●	●	●	●	–
750GG-D-2	750/150	gelb (2N)	15,5	○	○	○	○	○	○	○	○	○	–	–	–	–	–	○	–
750RSG-D-1	750/90	rosé	15,3	○	○	●	●	●	○	○	●	●	○	○	○	○	○	●	–
750RG-D-1	750/40	rot	15,1	○	○	○	○	●	●	○	●	○	○	○	○	○	○	○	–
750PWG-D-1	750/16% Pd	weiß	15,8	●	○	●	●	●	●	●	●	●	○	○	○	○	○	●	–
750PWG-D-2	750/14% Pd	weiß	16	○	○	○	○	○	○	○	○	○	–	–	–	–	–	○	–
750PWG-D-3	750/10% Pd	weiß	16	○	○	○	○	○	○	○	○	○	–	–	–	–	–	○	–
900GG-D-1	900/65	gelb	17,6	○	○	○	○	○	○	○	○	○	–	–	–	–	–	○	–
916RSG-D-1	916/-	rosé	17,9	○	○	○	○	○	○	○	○	○	–	–	–	–	–	○	–
999,9Au-D-1	999,9	Feingold	19,3	○	○	○	○	○	○	○	○	○	–	–	–	–	–	○	●
960PtC-D-1	960/40	PtCu	20,3	○	○	●	○	●	○	○	●	○	○	○	○	○	○	○	–
950PtW-D-1	950/50	PtW	21	○	○	○	○	○	○	○	○	○	–	–	–	–	–	○	–

LIEFERPROGRAMM DEGUSSA HALBZEUGE

Lote in Blechform; 0,3 mm stark

Metall	Name	Legierung	Farbe	Eigenschaft	Arbeitstemperatur in °C
AG	675AGL-D-H	675/-	weiß	streng	730
AG	600AGL-D-M	600/-	weiß	mittel	710
AG	600AGL-D-W	600/-	weiß	leicht	680
AU	333GGL-D-H	333/-	gelb	streng	720
AU	333GGL-D-W	333/-	gelb	leicht	680
AU	585GGL-D-H	585/-	gelb	streng	800
AU	585GGL-D-M	585/-	gelb	mittel	760
AU	585GGL-D-W	585/-	gelb	leicht	730
AU	585RGL-D-H	585/-	rot	streng	850
AU	585RGL-D-M	585/-	rot	mittel	820
AU	585WGL-D-H	585/-	weiß	streng	800
AU	585WGL-D-W	585/-	weiß	leicht	780
AU	750GGL-D-H	750/-	gelb	streng	815
AU	750GGL-D-M	750/-	gelb	mittel	780
AU	750GGL-D-W	750/-	gelb	leicht	750
AU	750RGL-D-H	750/-	rot	hart	820
AU	750RGL-D-M	750/-	rot	mittel	800
AU	750WGL-D-H	750/-	weiß	hart	840
AU	750WGL-D-W	750/-	weiß	weich	800